

Worldwide Leader In Advanced Cleaning Systems

DAIMER®

INDUSTRIES

SUPER MAX™ 12300 WS
with Daimer®'s Wet Sand Blaster System



DAIMER®
INDUSTRIES

www.daimer.com
16 Tower Office Park
Woburn, MA 01801
(800) 471-7157
sales@daimer.com

Daimer®'s industry-leading Super Max™ pressure washers are available in more than 400 models and configurations. The product line includes general purpose mobile machines, multi-gun stationary systems, pressure washers designed for indoor use and equipment manufactured for auto car detailing. The machines are available with pressure levels as high as 8000 psi and temperatures to 330°F. Daimer® also offers systems that support wet steam cleaning for cutting grease. Daimer®-only technologies available in Super Max™ pressure washers include: Long Hose Technology that supports hoses up to 300 feet in length and Auto Shutoff Technology™ for reduced system wear. Daimer® pressure washers are available in 50 Hz and 60 Hz configurations.



- With a 1 ½” spray pattern, this wet sand blaster is ideal for spot removal of rust, corrosion, paint layers, and other heavy deposits from metal surfaces, restoring them to shiny bare metal.
- Available in a variety of power configurations for worldwide requirements, including: 110-120V, 208V, 220-240V, 380V, 415V, 440-480V, and 575V; single and three phase; 50 or 60 Hz. Please contact us for pricing.
- Free Skid Configuration for Trailer Mounting

| Model | Super Max 12300 WS |
|-------------------------------|---|
| Pressure | 3000 PSI |
| Flow Rate | 5 GPM |
| Temp. Options | Cold, hot water, wet steam |
| Steam Temp. / Hot Water Temp. | Up to 330°F / 180°F - 210°F |
| Standard Power Method | Electric: 220V-240V, single phase, 60 Hz |
| Motor Size | Heavy duty 10.0 HP - NEMA |
| Minimum Generator Size | Contact Daimer |
| Gasoline/Diesel Fuel Capacity | N/A |
| Ignition System | Electronic direct spark |
| Heating Method | Propane (LPG) |
| Heating Fuel Capacity | 50 lb. empty tank included |
| Heater Exchange Coil | Heavy duty schedule 80 heating coil |
| Heater Response Time | Converts cold to hot water - approx. 30 seconds |
| Operating Time | Continuous use |
| Pump Drive Method | Shaft drive |
| Chemical Infusion | Yes – high pressure injection |
| Wand Included | Durable 3' trigger wand with quick disconnect |
| Nozzles Included | 0°, 15°, 25°, 40°, steam nozzles |
| Pressure Hose | 50' high pressure steam hose |
| Dimensions | 48" w. x 41" d. x 58" h. |
| Weight | 900 lbs. |
| AST® Technology | See the Super Max™ 12300 AST |
| Phosphatizing System | See the Super Max™ 12300 AF |
| Wet Sandblasting System | Yes |
| Multi-Gun Operation | Optional – call for pricing |
| Trailer Mount | Wheels removed |



www.daimer.com
 16 Tower Office Park
 Woburn, MA 01801
 (800) 471-7157
 sales@daimer.com