Worldwide Leader In Advanced Cleaning Systems

DAMER®

INDUSTRIES

SUPER MAX[™] 12840 AST with Automatic Shutoff Technology[™]







www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com Daimer®¢ industry-leading Super Maxï pressure washers are available in more than 400 models and configurations. The product line includes general purpose mobile machines, multi-gun stationary systems, pressure washers designed for indoor use and equipment manufactured for auto car detailing. The machines are available with pressure levels as high as 8000 psi and temperatures to 330°F. Daimer® also offers systems that support wet steam cleaning for cutting grease. Daimer®-only technologies available in Super Maxï pressure washers include: Long Hose Technology that supports hoses up to 300 feet in length and Auto Shutoff Technologyï for reduced system wear. Daimer® pressure washers are available in 50 Hz and 60 Hz configurations.





- Featuring AST® Automatic Shutoff Technologyï for trigger control of the motor & pump to reduce unnecessary wear & tear.
- Available in a variety of power configurations for worldwide requirements, including: 110-120V, 208V, 220-240V, 380V, 415V, 440-480V, and 575V; single and three phase; 50 or 60 Hz. Please contact us for pricing.
- Free Skid Configuration for Trailer Mounting

ModelSuper Max 12840 ASTPressure2000 PSIFlow Rate4 GPMTemp. OptionsCold, hot water, wet steamSteam Temp. / Hot Water Temp.Up to 330°F / 180°F - 210°FStandard Power MethodElectric: 230V, single phase, 60 HzMotor SizeHeavy duty 5.0 HP - NEMAMinimum Generator Size15000 wattsGasoline/Diesel Fuel CapacityN/AIgnition SystemElectronic direct spark
Flow Rate 4 GPM Temp. Options Cold, hot water, wet steam Steam Temp. / Hot Water Temp. Up to 330°F / 180°F - 210°F Standard Power Method Electric: 230V, single phase, 60 Hz Motor Size Heavy duty 5.0 HP - NEMA Minimum Generator Size 15000 watts Gasoline/Diesel Fuel Capacity N/A
Temp. Options Cold, hot water, wet steam Steam Temp. / Hot Water Temp. Up to 330°F / 180°F - 210°F Standard Power Method Electric: 230V, single phase, 60 Hz Motor Size Heavy duty 5.0 HP - NEMA Minimum Generator Size 15000 watts Gasoline/Diesel Fuel Capacity N/A
Steam Temp. / Hot Water Temp.Up to 330°F / 180°F - 210°FStandard Power MethodElectric: 230V, single phase, 60 HzMotor SizeHeavy duty 5.0 HP - NEMAMinimum Generator Size15000 wattsGasoline/Diesel Fuel CapacityN/A
Standard Power MethodElectric: 230V, single phase, 60 HzMotor SizeHeavy duty 5.0 HP - NEMAMinimum Generator Size15000 wattsGasoline/Diesel Fuel CapacityN/A
Motor Size Heavy duty 5.0 HP - NEMA Minimum Generator Size 15000 watts Gasoline/Diesel Fuel Capacity N/A
Minimum Generator Size 15000 watts Gasoline/Diesel Fuel Capacity N/A
Gasoline/Diesel Fuel Capacity N/A
Ignition System Electronic direct spark
-g
Heating Method Heating oil; diesel; kerosene
Heating Fuel Capacity 9 gallons
Heater Exchange Coil Heavy duty schedule 80 heating coil
Heater Response Time Converts cold to hot water - approx. 30 seconds
Operating Time Continuous use
Pump Drive Method Direct drive
Chemical Infusion Yes . high pressure injection
Wand Included Durable 3' trigger wand with quick disconnect
Nozzles Included 0°, 15°, 25°, 40°, steam nozzles
Pressure Hose 50' high pressure steam hose
Dimensions 25" w. x 32" d. x 42" h.
Weight 575 lbs.
AST® Technology Yes
Phosphatizing System See the Super Maxï 12840 AF
Wet Sandblasting System See the Super Maxï 12840 WS
Multi-Gun Operation Optional . call for pricing
Trailer Mount Wheels removed



www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com