

Worldwide Leader In Advanced Cleaning Systems

DAIMER®

INDUSTRIES

SUPER MAX™ 12860 WS
with Daimer®'s Wet Sand Blaster System



DAIMER®
INDUSTRIES

www.daimer.com
16 Tower Office Park
Woburn, MA 01801
(800) 471-7157
sales@daimer.com

Daimer®'s industry-leading Super Max™ pressure washers are available in more than 400 models and configurations. The product line includes general purpose mobile machines, multi-gun stationary systems, pressure washers designed for indoor use and equipment manufactured for auto car detailing. The machines are available with pressure levels as high as 8000 psi and temperatures to 330°F. Daimer® also offers systems that support wet steam cleaning for cutting grease. Daimer®-only technologies available in Super Max™ pressure washers include: Long Hose Technology that supports hoses up to 300 feet in length and Auto Shutoff Technology™ for reduced system wear. Daimer® pressure washers are available in 50 Hz and 60 Hz configurations.



- With a 1 ½” spray pattern, this wet sand blaster is ideal for spot removal of rust, corrosion, paint layers, and other heavy deposits from metal surfaces, restoring them to shiny bare metal.
- Available in a variety of power configurations for worldwide requirements, including: 110-120V, 208V, 220-240V, 380V, 415V, 440-480V, and 575V; single and three phase; 50 or 60 Hz. Please contact us for pricing.
- Free Skid Configuration for Trailer Mounting

Model	Super Max 12860 WS
Pressure	3000 PSI
Flow Rate	5 GPM
Temp. Options	Cold, hot water, wet steam
Steam Temp. / Hot Water Temp.	Up to 330°F / 180°F - 210°F
Standard Power Method	Electric: 220V-240V, single phase, 60 Hz
Motor Size	Heavy duty 10.0 HP - NEMA
Minimum Generator Size	Contact Daimer
Gasoline/Diesel Fuel Capacity	N/A
Ignition System	Electronic direct spark
Heating Method	Heating oil; diesel; kerosene
Heating Fuel Capacity	9 gallons
Heater Exchange Coil	Heavy duty schedule 80 heating coil
Heater Response Time	Converts cold to hot water - approx. 30 seconds
Operating Time	Continuous use
Pump Drive Method	Belt drive
Chemical Infusion	Yes – high pressure injection
Wand Included	Durable 3' trigger wand with quick disconnect
Nozzles Included	0°, 15°, 25°, 40°, steam nozzles
Pressure Hose	50' high pressure steam hose
Dimensions	41" w. x 48" d. x 58" h.
Weight	880 lbs.
AST® Technology	See the Super Max™ 12860 AST
Phosphatizing System	See the Super Max™ 12860 AF
Wet Sandblasting System	Yes
Multi-Gun Operation	Optional – call for pricing
Trailer Mount	Wheels removed



www.daimer.com
 16 Tower Office Park
 Woburn, MA 01801
 (800) 471-7157
 sales@daimer.com