

Worldwide Leader In Advanced Cleaning Systems

# DAIMER<sup>®</sup>

## INDUSTRIES

**SUPER MAX™ 12860**



**DAIMER<sup>®</sup>**  
INDUSTRIES

[www.daimer.com](http://www.daimer.com)  
16 Tower Office Park  
Woburn, MA 01801  
(800) 471-7157  
[sales@daimer.com](mailto:sales@daimer.com)

Daimer® industry-leading Super Maxi® pressure washers are available in more than 400 models and configurations. The product line includes general purpose mobile machines, multi-gun stationary systems, pressure washers designed for indoor use and equipment manufactured for auto car detailing. The machines are available with pressure levels as high as 8000 psi and temperatures to 330°F. Daimer® also offers systems that support wet steam cleaning for cutting grease. Daimer®-only technologies available in Super Maxi® pressure washers include: Long Hose Technology that supports hoses up to 300 feet in length and Auto Shutoff Technology® for reduced system wear. Daimer® pressure washers are available in 50 Hz and 60 Hz configurations.



- Upgradable to AST® - Automatic Shutoff Technology® for trigger control of the motor & pump to reduce unnecessary wear & tear.
- Available in a variety of power configurations for worldwide requirements, including: 110-120V, 208V, 220-240V, 380V, 415V, 440-480V, and 575V; single and three phase; 50 or 60 Hz. Please contact us for pricing.
- Free Skid Configuration for Trailer Mounting

| Model                         | Super Max 12860                                 |
|-------------------------------|---|
| Pressure                      | 3000 PSI  |
| Flow Rate                     | 5 GPM   |
| Temp. Options                 | Cold, hot water, wet steam                      |
| Steam Temp. / Hot Water Temp. | Up to 330°F / 180°F - 210°F                     |
| Standard Power Method         | Electric: 220V-240V, single phase, 60 Hz        |
| Motor Size                    | Heavy duty 10.0 HP - NEMA                       |
| Minimum Generator Size        | Contact Daimer                                  |
| Gasoline/Diesel Fuel Capacity | N/A   |
| Ignition System               | Electronic direct spark                         |
| Heating Method                | Heating oil; diesel; kerosene                   |
| Heating Fuel Capacity         | 9 gallons                                       |
| Heater Exchange Coil          | Heavy duty schedule 80 heating coil             |
| Heater Response Time          | Converts cold to hot water - approx. 30 seconds |
| Operating Time                | Continuous use                                  |
| Pump Drive Method             | Belt drive                                      |
| Chemical Infusion             | Yes . high pressure injection                   |
| Wand Included                 | Durable 3' trigger wand with quick disconnect   |
| Nozzles Included              | 0°, 15°, 25°, 40°, steam nozzles                |
| Pressure Hose                 | 50' high pressure steam hose                    |
| Dimensions                    | 41" w. x 48" d. x 58" h.                        |
| Weight                        | 880 lbs.  |
| AST® Technology               | See the Super Maxi® 12860 AST                   |
| Phosphatizing System          | See the Super Maxi® 12860 AF                    |
| Wet Sandblasting System       | See the Super Maxi® 12860 WS                    |
| Multi-Gun Operation           | Optional . call for pricing                     |
| Trailer Mount                 | Wheels removed                                  |



www.daimer.com  
 16 Tower Office Park  
 Woburn, MA 01801  
 (800) 471-7157  
 sales@daimer.com