Worldwide Leader In Advanced Cleaning Systems



SUPER MAX™ 15450







www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com Daimer®c industry-leading Super Maxi pressure washers are available in more than 400 models and configurations. The product line includes general purpose mobile machines, multi-gun stationary systems, pressure washers designed for indoor use and equipment manufactured for auto car detailing. The machines are available with pressure levels as high as 8000 psi and temperatures to 330°F. Daimer® also offers systems that support wet steam cleaning for cutting grease. Daimer®-only technologies available in Super Maxi pressure washers include: Long Hose Technology that supports hoses up to 300 feet in length and Auto Shutoff Technologyi for reduced system wear. Daimer® pressure washers are available in 50 Hz and 60 Hz configurations.





 Available in a variety of power configurations for worldwide requirements, including: 110-120V, 208V, 220-240V, 380V, 415V, 440-480V, and 575V; single and three phase; 50 or 60 Hz. Please contact us for pricing.

Model Pressure Flow Rate Temp. Options Steam Temp. / Hot Water Temp. Standard Power Method Motor Size Minimum Generator Size	Super Max 15450 700 PSI (48.3 bar) 11.4 LPM Cold, hot water, wet steam Up to 165°C / 82.2°C . 98.9°C Electric: 110V-120V, single phase, 50 Hz
Flow Rate Temp. Options Steam Temp. / Hot Water Temp. Standard Power Method Motor Size	11.4 LPM Cold, hot water, wet steam Up to 165°C / 82.2°C . 98.9°C
Temp. Options Steam Temp. / Hot Water Temp. Standard Power Method Motor Size	Cold, hot water, wet steam Up to 165°C / 82.2°C . 98.9°C
Steam Temp. / Hot Water Temp. Standard Power Method Motor Size	Up to 165°C / 82.2°C . 98.9°C
Standard Power Method Motor Size	•
Motor Size	Electric: 110\/_120\/_single_phase_50 Hz
	Lieuno. 110v-120v, single phase, 30 Hz
Minimum Generator Size	Heavy duty 1.5 HP - NEMA
	N/A
Gasoline/Diesel Fuel Capacity	N/A
Ignition System	Electronic direct spark
Heating Method Heati	ing oil; diesel; kerosene; natural gas; propane
Heating Fuel Capacity	34 liters
Heater Exchange Coil	Heavy duty schedule 80 heating coil
Heater Response Time Con	overts cold to hot water - approx. 30 seconds
Operating Time	Continuous use
Pump Drive Method	Direct drive
Chemical Infusion	Yes . high pressure injection
Wand Included Durat	ble 91.4cm trigger wand with quick disconnect
Nozzles Included	0°, 15°, 25°, 40°, steam nozzles
Pressure Hose	15.2m high pressure steam hose
Dimensions	132cm x 58.5cm x 127cm
Weight	431 kg
AST® Technology	N/A
Phosphatizing System	N/A
Wet Sandblasting System	N/A
Multi-Gun Operation	Optional . call for pricing
Trailer Mount	N/A



www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com