

Worldwide Leader In Advanced Cleaning Systems

DAIMER®

INDUSTRIES

VAPOR-FLO® 7375



DAIMER®
INDUSTRIES

www.daimer.com
16 Tower Office Park
Woburn, MA 01801
(800) 471-7157
sales@daimer.com

The Vapor-Flo® line of pressure offers all-electric performance designed for reduced noise and no fumes. The machines are heated and powered with electricity and are available in more than 80 configurations designed to meet the needs of domestic and overseas customers. The models include stationary models for fixed applications and several mobile models in different case designs. Daimer® case designs include a chemical resistant stainless steel housing and top loading model that allows for manual refills and operation away from a fixed water source. All Vapor-Flo® machines are covered by company backed warranties for water pumps, motors and other parts.



- **Electric powered and electric heated** for maximum efficiency and user convenience.
- All electric pressure washers **generate no exhaust**. Their clean-burning operation is ideal for indoor commercial and industrial applications.
- This **220V-240V, single phase, 50 Hz machine** is also available in 220V-240V, single phase, 60 Hz. See the Vapor-Flo® 8275.
- **Top temperatures reach up to 96.1°C** for optimum cleaning power.

Model	Vapor-Flo 7375
Pressure	1700 PSI (117 bar)
Flow Rate	1.5 LPM
Temp. Options	Cold, hot water
Hot Water Temp.	Up to 96.1°C
Standard Power Method	Electric: 220V-240V, three phase, 50 Hz / 440V, three phase 50 Hz
Optional Power Method	Electric: 220V-240V, three phase, 60 Hz
Motor Size	Heavy duty 1.0 HP
Minimum Generator Size	Contact Daimer
Gasoline/Diesel Fuel Capacity	N/A
Ignition System	N/A
Heating Method	Electric – 10.0 kW
Heating Fuel Capacity	N/A
Heater Exchange Coil	High-pressure stainless steel
Heater Response Time	Converts cold to hot water - approx. 20 seconds
Operating Time	Continuous use
Pump Drive Method	Direct drive
Chemical Infusion	Yes - siphon type standard/foam lance injection
Wand Included	Durable 2.5' trigger wand with quick disconnect
Nozzles Included	15° stainless steel pressure nozzle with incorporated filter
Pressure Hose	9.8m high pressure, double layered hose
Dimensions	63.5 cm w. x 88.9 cm d. x 81.3 cm h.
Weight	74.8 kg
Wall Mount	Yes
Trailer Mount	N/A



www.daimer.com
 16 Tower Office Park
 Woburn, MA 01801
 (800) 471-7157
 sales@daimer.com