Worldwide Leader In Advanced Cleaning Systems



VAPOR-FLO® 8375





www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com The Vapor-Flo® line of pressure offers all-electric performance designed for reduced noise and no fumes. The machines are heated and powered with electricity and are available in more than 80 configurations designed to meet the needs of domestic and overseas customers. The models include stationary models for fixed applications and several mobile models in different case designs. Daimer® case designs include a chemical resistant stainless steel housing and top loading model that allows for manual refills and operation away from a fixed water source. All Vapor-Flo® machines are covered by company backed warrantees for water pumps, motors and other parts.



- Electric powered and electric heated for maximum efficiency and user convenience.
- All electric pressure washers generate no exhaust.
 Their clean-burning operation is ideal for indoor commercial and industrial applications.
- This 220V-240V, single phase, 60 Hz machine is also available in 220V-240V, single phase, 50 Hz. See the Vapor-Flo® 7475.
- Top temperatures reach up to 175°F for optimum cleaning power.

Model Pressure Flow Rate Temp. Options	Vapor-Flo 8375 1700 PSI 0.6 GPM Cold, hot water
Flow Rate	0.6 GPM Cold, hot water
1 10 11 11010	Cold, hot water
Temp. Options	·
	Un to 175°E
Hot Water Temp.	Up to 175°F
Standard Power Method	Electric: 220V-240V, three phase, 60 Hz / 440V, three
	phase 60 Hz
Optional Power Method	Electric: 220V-240V, three phase, 50 Hz / 440V, three
	phase, 50 Hz
Motor Size	Heavy duty 2.0 HP
Minimum Generator Size	Contact Daimer
Gasoline/Diesel Fuel Capacity	N/A
Ignition System	N/A
Heating Method	Electric – 10.0 kW
Heating Fuel Capacity	N/A
Heater Exchange Coil	High-pressure stainless steel
Heater Response Time	Converts cold to hot water - approx. 20 seconds
Operating Time	Continuous use
Pump Drive Method	Direct drive
Chemical Infusion	Yes - siphon type standard/foam lance injection
Wand Included	Durable 2.5' trigger wand with quick disconnect
Nozzles Included	25° stainless steel pressure nozzle with incorporated filter
Pressure Hose	32' high pressure, double layered hose
Dimensions	25" w. x 35" d. x 32" h.
Weight	165 lbs.
Wall Mount	Yes
Trailer Mount	N/A



www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com