

VAPOR-FLO® 8910





www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com The Vapor-Flo® line of pressure offers all-electric performance designed for reduced noise and no fumes. The machines are heated and powered with electricity and are available in more than 80 configurations designed to meet the needs of domestic and overseas customers. The models include stationary models for fixed applications and several mobile models in different case designs. Daimer® case designs include a chemical resistant stainless steel housing and top loading model that allows for manual refills and operation away from a fixed water source. All Vapor-Flo® machines are covered by company backed warrantees for water pumps, motors and other parts.



- Electric powered and electric heated for maximum efficiency and user convenience.
- All electric pressure washers generate no exhaust. Their clean-burning operation is ideal for indoor commercial and industrial applications.
- This 220V-240V, single phase, 60 Hz machine is also available in 220V-240V, single phase, 50 Hz. See the Vapor-Flo® 7910.
- Top temperatures reach up to 205°F for optimum cleaning power.

ModelVapor-Flo 8910Pressure2030 PSIFlow Rate1.4 GPMTemp. OptionsCold, hot waterHot Water Temp.Up to 205°FStandard Power MethodElectric: 440V, three phase 60 Hz	
Flow Rate1.4 GPMTemp. OptionsCold, hot waterHot Water Temp.Up to 205°F	
Temp. OptionsCold, hot waterHot Water Temp.Up to 205°F	
Hot Water Temp. Up to 205°F	
Standard Power Method Flectric: 440V three phase 60 Hz	
Optional Power Method Electric: 400V, three phase 50 Hz / 480V, three phase 60 Hz	е
Motor Size Heavy duty 3.0 HP	
Minimum Generator Size Contact Daimer	
Gasoline/Diesel Fuel Capacity N/A	
Ignition System N/A	
Heating Method Electric – 25.0 kW	
Heating Fuel Capacity N/A	
Heater Exchange Coil High-pressure stainless steel	
Heater Response Time Converts cold to hot water - approx. 20 seconds	
Operating Time Continuous use	
Pump Drive Method Direct drive	
Chemical Infusion Yes - siphon type standard/foam lace injection	
Wand Included Durable 2.5' trigger wand with quick disconnect	
Nozzles Included 25° stainless steel pressure nozzle with incorporated filte	lter
Pressure Hose 32' high pressure, double layered hose	
Dimensions 25" w. x 35" d. x 32" h.	
Weight 183 lbs.	
Wall Mount Yes	
Trailer Mount N/A	



www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com