

Worldwide Leader In Advanced Cleaning Systems

# DAIMER®

INDUSTRIES

**XTREME POWER® HSC 14250**



**DAIMER®**  
INDUSTRIES

[www.daimer.com](http://www.daimer.com)  
16 Tower Office Park  
Woburn, MA 01801  
(800) 471-7157  
[sales@daimer.com](mailto:sales@daimer.com)

Daimer®'s XTreme Power® HSC line includes more than 20 models designed for industrial, commercial and residential applications. The machines is composed of a variety of machines designed for optimum performance on a variety of surfaces. The HSC line includes: self-contained floor cleaners, high-performance units for cleaning up after water damage as well as machines with powered spinning heads. The powered spinning heads come in two sizes, 9-inch and 19-inch, for large and small applications. Several machines are optimized to handle deep-cleaning on porous tile floors. All the machines are covered by Daimer®'s exclusive warrantee options for years of worry free operation.



The XTreme Power® HSC 14250 can be used as several machines in one:

- **Multi-Surface, Portable 1000 PSI Hard Surface Spinner Cleaning Machine** - Configured as is.
- **Commercial Steam Pressure Washer** - 1000 PSI, up to 2.5 GPM. Pressure washer wand included.
- **Commercial Wall Cleaning System** – With optional 9" spinner head placed in hands or optional squeegee wand.
- **Commercial Sludge Extractor** - Powerful 30 GPM for water damage restoration.

Model	XTreme Power HSC 14250
Pressure	1000 psi
Flow Rate	2.5 GPM
Temperature Options	Cold water, hot water, wet steam (steam cannot be used with spinner head)
Temperature (Hot/Steam)	Up to 210°F / up to 330°F (not for use with spinner head)
Heating Method	Propane
Propane Tanks	40 lb. empty tank included
Heater Exchange Coil	High-pressure stainless steel
Spinner Diameter/Length/RPM	19 inches / 46 inches / 1000 RPM
Standard Power Method: Pressure Washer	Electric: 110-120V, single phase, 60 Hz
Motor Size: Pressure Washer	Heavy Duty 1.5 HP NEMA
Ignition System	N/A
Operating Time	Continuous Use
Continuous Water Feed	Yes. Connect hose directly to pressure washer.
Recovery Tank Size	10 gallons
Automatic Dump	Yes – Auto dump can be turned off if not required
Dumping Capacity	30 gallons/minute
Air Flow	212 cfm
Water Lift	147 inches
Motor: Extractor	Two - 3 stage vacuum motors
Power: Extractor	Electric: 120V
Heater Response Time	Cold water to hot water in approx. 30 seconds
Chemical Infusion	Yes - Siphon type standard
Hoses: Vacuum/Dump/Steam	50' vacuum, 50' dump, 25' steam hoses included
Pressure Nozzles	0° (blast), 15°, 25°, 40°, steam nozzles
Wands Included	Durable 3' pressure wand with quick disconnect, 14.5" extraction squeegee wand
Optional Wands	12" 4-jet squeegee wand, 18" squeegee wand with 6 internal jets, 9" motorized spinner
Housing: Pressure Washer/Extractor	Pressure Washer: Steel - powder-coated, high-gloss, chip/chemical resistant Extractor: Heavy duty fiber composite
Color: Pressure Washer/Extractor	White / Blue or Red
Dimensions: Pressure Washer/Extractor	23" w. x 30" d. x 45" h. / 16" w. 32" h. 21" l.
Weight: Pressure Washer/Extractor	250 lbs. / 90 lbs.