

Worldwide Leader In Advanced Cleaning Systems

DAIMER[®]

INDUSTRIES

XTREME POWER[®] HSC 17800



DAIMER[®]
INDUSTRIES

www.daimer.com
16 Tower Office Park
Woburn, MA 01801
(800) 471-7157
sales@daimer.com

Daimer®'s XTreme Power® HSC line includes more than 20 models designed for industrial, commercial and residential applications. The machines is composed of a variety of machines designed for optimum performance on a variety of surfaces. The HSC line includes: self-contained floor cleaners, high-performance units for cleaning up after water damage as well as machines with powered spinning heads. The powered spinning heads come in two sizes, 9-inch and 19-inch, for large and small applications. Several machines are optimized to handle deep-cleaning on porous tile floors. All the machines are covered by Daimer®'s exclusive warrantee options for years of worry free operation.



The XTreme Power® HSC 17800 can be used as several machines in one:

- **Multi-Surface, Portable 1000 PSI Hard Surface Spinner Cleaning Machine** - Configured as is.
- **Commercial Steam Pressure Washer** - 1000 PSI, up to 2 GPM. Pressure washer wand included.
- **Commercial Wall Cleaning System** – With optional 9" spinner head placed in hands or optional squeegee wand.
- **Commercial Sludge Extractor** - Powerful 30 GPM for water damage restoration.

| Model | XTreme Power HSC 17800 |
|---|--|
| Pressure | 1000 psi |
| Flow Rate | 2 GPM |
| Temperature Options | Cold water, hot water, wet steam (steam cannot be used with spinner head) |
| Temperature (Hot/Steam) | Up to 180°F - 210°F / up to 330°F (not for use with spinner head) |
| Heating Method | Heating oil; diesel; kerosene |
| Propane Tanks | N/A |
| Heater Exchange Coil | Heavy duty schedule 80 heating coil |
| Spinner Diameter/Length/RPM | 19 inches / 46 inches / 1000 RPM |
| Standard Power Method: Pressure Washer | Electric: 110V-120V, single phase, 60 Hz |
| Motor Size: Pressure Washer | Heavy duty 1.5 HP NEMA |
| Ignition System | Electronic direct spark |
| Operating Time | Continuous Use |
| Continuous Water Feed | Yes. Connect hose directly to pressure washer. |
| Recovery Tank Size | 10 gallons |
| Automatic Dump | Yes – Auto dump can be turned off if not required |
| Dumping Capacity | 30 gallons/minute |
| Air Flow | 212 cfm |
| Water Lift | 147 inches |
| Motor: Extractor | Two - 3 stage vacuum motors |
| Power: Extractor | Electric: 120V |
| Heater Response Time | Cold water to hot water in approx. 30 seconds |
| Chemical Infusion | Yes – High pressure injection |
| Hoses: Vacuum/Dump/Steam | 50' vacuum, 50' dump, 50' steam hoses included |
| Pressure Nozzles | 0° (blast), 15°, 25°, 40°, steam nozzles |
| Wands Included | Durable 3' pressure wand with quick disconnect, 14.5" extraction squeegee wand |
| Optional Wands | 12" 4-jet squeegee wand, 18" squeegee wand with 6 internal jets, 9" motorized spinner |
| Housing: Pressure Washer/Extractor | Pressure Washer: Steel - powder-coated, high-gloss, chip/chemical resistant Extractor: Heavy duty fiber composite |
| Color: Pressure Washer/Extractor | Black and silver / Blue or Red |
| Dimensions: Pressure Washer/Extractor | 25" w. x 32" d. x 42" h. / 16" w. 32" h. 21" l. |
| Weight: Pressure Washer/Extractor | 450 lbs. / 90 lbs. |